

DRAWING LIST		SCALE
A000	COVER SHEET & DRAWING LIST	NTS
A001	PROJECT DESCRIPTION & SITE LOCATION PLAN	NTS/1:1000
A002	EXISTING SITE PLAN	1:100
A003	PROPOSED SITE PLAN	1:100
A004	AVERAGE GRADE CALCULATIONS	1:100
A100	LEVEL 0 PARKING PLAN	1:100
A101	LEVEL 1 PLAN	1:100
A102	LEVEL 2 PLAN	1:100
A103	LEVEL 3 PLAN	1:100
A104	LEVEL 4 PLAN	1:100
A105	LEVEL 5 PLAN	1:100
A106	LEVEL 6 PLAN	1:100
A107	ROOF PLAN	1:100
A201	EAST & SOUTH ELEVATIONS	1:150
A202	NORTH & WEST ELEVATIONS	1:150
A203	HERITAGE ELEVATION & PLAN STUDY	1:100
A204	FACADE STUDIES	1:50
A251	STREETSCAPE ELEVATIONS	NTS
A301	SECTIONS LOOKING WEST	1:150
A302	SECTIONS LOOKING EAST	1:150
A303	SECTIONS LOOKING NORTH	1:150
A304	SECTIONS LOOKING NORTH/SOUTH	1:150
A305	SECTIONS LOOKING SOUTH	1:150
A308	STREETSCAPE CROSS SECTION	1:50
A800	FSR LEGEND	1:100
A801	FSR - LEVEL 1	1:100
A802	FSR - LEVEL 2	1:100
A803	FSR - LEVEL 3	1:100
A804	FSR - LEVEL 4	1:100
A805	FSR - LEVEL 5	1:100
A806	FSR - LEVEL 6	1:100
A811	VIEW NORTHWEST FROM CORNER OF PANDORA & COOK	NTS
A812	VIEW WEST THROUGH RESIDENTIAL MEWS	NTS
A813	VIEW SOUTHWEST FROM COOK STREET	NTS
A814	VIEW EAST TO COURTYARD	NTS
A815	BALCONY STUDY	NTS
A817	ADJACENT PROPERTY STUDY	NTS
A821	SOLAR IMPACT ANALYSIS	NTS
A822	ILLUMINANCE ANALYSIS	NTS



MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8

2020-03-20 REVISED FOR REZONING
2019-10-30 REVISED FOR REZONING
2019-09-13 REVISED FOR REZONING
2019-05-15 ISSUED FOR REZONING

DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001

A000
COVER SHEET

PROJECT NARRATIVE

The Parkway Revitalization and Development is located at Pandora Avenue & Cook Street, at the site of what is known to the community as the Wellburns Building. Originally named Parkway Apartments, the two-storey masonry building was constructed in 1911 by William Ridgway-Wilson. At the corner of the North Park neighbourhood, the building is a gateway feature to both the neighbourhood and the centre of Victoria.

The new development proposes a 4 & 6 storey volume stepping back from the existing heritage building to the north & west, and from Franklin Green Park to the south & east. 103 purpose-built rental apartments are proposed with a retail / commercial space being maintained on the existing ground floor of the Wellburn's Building and the addition of a cafe space in the ground floor of the new addition facing Cook Street. A mews separating the historic and modern buildings at street level serves as the residential entrance to the building and provides access to a west facing courtyard. Public access to and from Franklin Green Park is provided through a wide pedestrian walkway along the north edge of the site. One level of underground parking will be provided below the project site.

A priority of the project is to conserve the heritage value of the Wellburn's building through retaining 50% of the existing volume, including the historic facades facing Pandora Ave & Cook St and the north-east wall facing the residential mews. All character-defining

elements in these locations will be preserved along with any in-kind repairs, as required. The original use of the building will remain with opportunities for multiple retail spaces on the ground floor & residential suites above. The building will be Designated Heritage with the Heritage Registry.

The new development will be clad in a large format, pearl coloured, ultra high performance concrete panel. It will borrow elements from its historic counterpart, including the running bond pattern of the glazed white brick, the rhythm, proportion & angles of the projecting oriel windows and the recessed entryways of the existing storefronts.

To create a strong visual connection with the surrounding context, juliet balconies will be provided in the living spaces of the suites directly facing Franklin Green Park & Harris Green Park. An accessible roof deck will also be provided for all residential tenants of the building, facing onto Franklin Green Park.

PROJECT NAME

Parkway

PROJECT ADDRESS

1050 Pandora Ave + 1518 Cook Street

LEGAL DESCRIPTION

Lots 1 and 2, Suburban Lot 15, Victoria, V1P 73211

PROJECT TEAM

OWNER

Pandora Cook Development Corp.

District Developments Corp.

200-8809 Heather Street, Vancouver, BC, V6P 3T1

Primary Contact

Andrew Rennison
604-736-1866

AGENT

DISTRICT DEVELOPMENTS CORP.

200-8809 Heather Street, Vancouver, BC, V6P 3T1

Primary Contact

Jessica Gibson
604-322-5762

ARCHITECT

MGA | Michael Green Architecture
1535 West 3rd Avenue, Vancouver, BC, V6J 1J8

Architect

Michael Green

Contact

Jordan Van Dijk
604-336-4770

PROPOSED ZONING

New Site-Specific Zone

Changed from R-2 (Two Family Dwelling District) at 1518 Cook Street, and CA-1 (Pandora Avenue Special Commercial District) at 1050 Pandora Avenue.

SITE AREA

2879 m²

AVERAGE GRADE

27.54m (See A004 for average grade calculations)

Note that the project ground floor is set at a geodetic elevation of 27.56m and building levels are dimensioned from that elevation.

PROPOSED HEIGHT

20.22m taken from average grade. Note that 321mm parapet is excluded from proposed height.

ALLOWABLE HEIGHT

30m/ 18-storeys per OCP

APPLICABLE BUILDING CODE

BCBC 2018

STREETS FACING

Pandora Avenue to the South
Cook Street to the East

OCCUPANCY CLASSIFICATIONS

3.2.2.50, Group C, up to 6 Storeys,

Sprinklered- Residential Occupancies

3.2.2.50, Group E, up to 6 Storeys,

Sprinklered- Mercantile Occupancies,

Located below the third storey.

3.2.2.82 Group F, Division 3, Up to 6 Storeys,

Sprinklered- Below Grade Parkade.

AREA CALCULATIONS

LEVEL 0 2,713.6 m² CITY m2 L1 L2 L3 L4 L5 L6 TOTALLEVEL 1 1832.82 m² STUDIO A 56.0 1 1 1 1 2
LEVEL 2 1990.02 m² STUDIO B 52.6 1 1 1 1 2
LEVEL 3 1408.55 m² ST & DEN A 66.0 4
LEVEL 4 1399.30 m² ST & DEN B 72.7 1
LEVEL 5 921.02 m² ST & DEN C 57.7 1
LEVEL 6 860.58 m² ST & DEN D 53.6 1

PROPOSED FSR

8,412.3 m²ALLOWABLE FSR 9,330 m²

PROPOSED FSR RATIO 2.9

ALLOWABLE FSR RATIO 3.3

UNIT TYPES No# %

1 BED A 52.1 1 1 1 1 4
1 BED B 52.8 1 1 1 1 4
1 BED C 56.1 1
1 BED D 48.3 1
1 BED E 48.6 1 1 1 3
1 BED F 51.6 5
1 BED G 46.8 1 1 2
1 BED H 36.2 1
1 BED I 51.1 5 5 10
1 BED J 36.7 1 1 1 4
1 BED K 47.8 1 1 1 4
1 BED L 53.4 1
1 BED M 45.0 1
1 BED N 48.4 1
1 BED O 49.0 1
1 BED P 48.6 1
1 BED Q 49.0 1 1 1
1 BED R 51.9 1
1 BED S 51.1 1
1 BED T 45.0 1

TOTAL 103

1 BED N 48.4 1
1 BED O 49.0 1
1 BED P 48.6 1
1 BED Q 49.0 1 1 1
1 BED R 51.9 1
1 BED S 51.1 1
1 BED T 45.0 1

PROPOSED HEIGHT

20.221m

1 BED Q 49.0 1 1 1
1 BED R 51.9 1
1 BED S 51.1 1
1 BED T 45.0 1

TOTAL RESIDENTIAL AREA

5884 m²1 B&D A 61.5 1
1 B&D B 51.6 1
1 B&D C 62.2 1 2 2 2 7
1 B&D D 59.1 1
1 B&D E 51.4 1 1 1 2
1 B&D F 54.2 1 1 1 2
1 B&D G 51.0 1
1 B&D H 58.0 1
1 B&D I 62.2 1 1 1 3
1 B&D J 93.9 1
1 B&D K 81.2 1
1 B&D L 73.0 2
1 B&D M 68.7 1

TOTAL COMMERCIAL AREA

1054 m²2 BED A 72.5 1
2 BED B 68.8 1
2 BED C 73.5 1
2 BED D 60.0 1 1 1 3
2 BED E 79.5 1
2 BED F 67.2 1 1 1 3
2 BED G 75.4 1

ORIGINAL HERITAGE BUILDING AREA

1891.9m²2 BED A 90.8 1
2 BED B 96.1 1 1 1 2
2 BED C 76.1 1

TOTAL AREA TO BE RETAINED

947.6m² | 50%2 BED A 90.8 1
2 BED B 96.1 1 1 1 2
2 BED C 76.1 1

TOTAL BIKE PARKING

172

2 BED A 90.8 1
2 BED B 96.1 1 1 1 2
2 BED C 76.1 1

TOTAL UNITS

8 24 21 21 15 14 103

PARKING CALCULATIONS

RESIDENTIAL PARKING

Parking Rate 0.50 # of Units 5 Required 2.5 Provided 3
45-70m² 0.60 85 51.0 23
>70m² 1.00 13 13.0 7
TOTAL RESIDENTIAL PARKING 67 33

VISITOR PARKING

Visitor Parking 0.10 # of Units 103 Required 10 Provided 4

COMMERCIAL PARKING

Retail/ Grocery 1 / 80m² Total Area (m²) 888 11 2
Restaurant 1 / 40m² 221.7 6 3
TOTAL COMMERCIAL PARKING 17 5

CARSHARE PARKING

Modo Carshare Parking Stalls TOTAL PARKING 93 44

BIKE PARKING | LONG TERM

Residential 1 / unit <45m² # of Units 5 Required 5 Provided 20
1.25/unit >45m² 98 123 122Restaurant 1 / 400m² Total Area (m²) 221.7 1 6
1 / 200m² 888 5 6
TOTAL LONG TERM BIKE PARKING 133 154


BIKE PARKING | SHORT TERM


Residential .1 / unit Total Area (m²) 103 Total Units 10 Required 10 Provided 10
Restaurant 1 / 100m² 221.7 3 3
Retail/ Grocery 1 / 200m² 888 5 5
TOTAL SHORT TERM BIKE PARKING 18 18MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J82020-03-20 3 REVISED FOR REZONING
2019-10-30 2 REVISED FOR REZONING
2019-09-13 1 REVISED FOR REZONING
2019-05-15 0 ISSUED FOR REZONING

DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001A001
PROJECT DESCRIPTION





MICHAEL GREEN ARCHITECTURE
635 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8

N

020-03-20  REVISED FOR REZONING

019-10-30 2 REVISED FOR REZONING

REVISED FOR REZONING

09-09-13 REVISED FOR REZONING

0919-05-15 ISSUED FOR REZONING

DATE	REVISION	DESCRIPTION
------	----------	-------------

DATE	REVISION	DESCRIPTION
------	----------	-------------

© 2010 PARKWAY

PARKWAY

EDWARD DRUMMOND LUCE GOALS

950 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC

018-001

4 3 2 1

ΛΟΟΠΑ


A004

AVVERAGE GRADE CALC


AVERAGE GRADE CALC.

A004

AVERAGE GRADE CALC







A105
LEVEL 5 PLAN

1
A105 1:100

2020-03-20 REVISED FOR REZONING
2019-10-30 REVISED FOR REZONING
2019-09-13 REVISED FOR REZONING
2019-05-15 ISSUED FOR REZONING

DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001


MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8



UNIT CALCULATIONS		CITY	m ²	L1	L2	L3	L4	L5	L6	TOTAL
STUDIO A	52.1	STUDIO B	52.6		1	1		1	1	2
ST & DEN A	66.0	ST & DEN B	72.7		4					4
ST & DEN C	57.7	ST & DEN C	53.6		1	1	1	1	1	1
1 BED A	52.1	1 BED B	52.8	1	1	1	1	1	1	4
1 BED C	56.1	1 BED D	48.3		1	1				2
1 BED E	48.6	1 BED F	51.6		1	1	1	1	1	3
1 BED G	46.8	1 BED H	36.2		1	1	1	1	1	10
1 BED I	51.1	1 BED J	36.7		1	1	1	1	1	4
1 BED K	47.8	1 BED L	53.4		1	1	1	1	1	1
1 BED M	45.0	1 BED N	46.4		1	1				1
1 BED O	49.0	1 BED P	48.6		1	1				1
1 BED Q	49.0	1 BED R	51.9	1						1
1 BED S	51.1	1 BED T	45.0		1	1				1
1 B&D A	61.5	1 B&D B	51.6	1						1
1 B&D C	62.2	1 B&D D	59.1	1	2	2	2	2		7
1 B&D E	51.4	1 B&D F	54.2		1	1	1	1	1	2
1 B&D G	51.0	1 B&D H	38.0		1	1	1	1	1	1
1 B&D I	62.2	1 B&D J	93.9		1	1				1
1 B&D K	81.2	1 B&D L	73.0	2	1					2
1 B&D M	68.7	1 B&D N	75.4		1	1	1	1	1	1
2 BED A	72.5	2 BED B	68.8		1					1
2 BED C	73.5	2 BED D	60.0	1	1	1	1	1	3	
2 BED E	79.5	2 BED F	67.2	1	1	1	1	1	3	
2 BED G	75.4	2 BED H	67.2		1	1	1	1	1	1
2 BED I	90.8	2 BED J	96.1	1	1	1	1	1	2	
2 BED K	76.1									1
TOTAL UNITS										
8	24	21	21	15	14	103				

13'-0 1/4" [3970mm] 175'-0" [53340mm] 25'-8" [7822mm] 43'-0 3/4" [1325mm] 65'-0" [19822mm] 65'-0" [19822mm] 44'-3 1/4" [13496mm] 13'-5" [4086mm] 175'-0" [53340mm] 24'-11" [7600mm] 52'-0" [15856mm] 43'-0 3/4" [1325mm]

A105
LEVEL 5 PLAN



UNIT CALCULATIONS								
CITY	m ²	L1	L2	L3	L4	L5	L6	TOTAL
STUDIO A	56.0			1	1			2
STUDIO B	52.6		1	1	1		1	2
ST & DEN A	66.0			4				4
ST & DEN B	72.7		1				1	1
ST & DEN C	57.7			1				1
ST & DEN D	53.6			1				1
1 BED A	52.1	1	1	1	1			4
1 BED B	52.8	1	1	1	1			4
1 BED C	56.1		1					1
1 BED D	48.3		1					1
1 BED E	48.6		1	1	1			3
1 BED F	51.6		1					10
1 BED G	46.8		1	1	1			2
1 BED H	36.2			5			1	1
1 BED I	51.1			1	1	1	4	10
1 BED J	36.7		1	1	1	1		1
1 BED K	47.8			1	1	1		1
1 BED L	53.4						1	1
1 BED M	45.0						1	1
1 BED N	46.4							1
1 BED O	49.0							1
1 BED P	48.6							1
1 BED Q	49.0						1	1
1 BED R	51.9		1					1
1 BED S	51.1						1	1
1 BED T	45.0							1
1 BED U	51.5	1						1
1 BED V	51.6		1	2	2	2		7
1 BED W	52.2		1					1
1 BED X	59.1							1
1 BED Y	54.1							1
1 BED Z	54.2		1	1	1			2
1 BED A	51.0							1
1 BED B	58.0		1	1	1			1
1 BED C	62.2		1	1	1			3
1 BED D	93.9		1					1
1 BED E	81.2		1					1
1 BED F	73.0	2						2
1 BED G	68.7	1						1
2 BED A	72.5						1	1
2 BED B	68.8		1					1
2 BED C	73.5		1	1	1			3
2 BED D	60.0		1	1	1			1
2 BED E	79.5		1					1
2 BED F	67.2		1	1	1			3
2 BED G	75.4						1	1
2 BED H	90.8		1					1
2 BED I	96.1		1	1	1			2
2 BED J	76.1		1					1
TOTAL UNITS	8	24	21	21	15	14	103	

MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8




- 2020-03-20 REVISED FOR REZONING
- 2019-10-30 REVISED FOR REZONING
- 2019-09-13 REVISED FOR REZONING
- 2019-05-15 ISSUED FOR REZONING

DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001



MICHAEL GREEN ARCHITECTURE

635 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8

5° N

020-03-20		REVISED FOR REZONING
019-10-30		REVISED FOR REZONING
019-09-13		REVISED FOR REZONING
019-05-15		ISSUED FOR REZONING

DATE	REVISION	DESCRIPTION
------	----------	-------------

PARKWAY

950 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
V8W 0E1

A107

ROOF PLAN

MATERIALITY



PEARL COLOURED ULTRA-HIGH PERFORMANCE CONCRETE PANEL



TRANSPARENT GLAZING WITH DARK GREY FRAMES



EXISTING WHITE GLAZED BRICK



EXISTING ORNAMENTAL DETAILING RESTORED TO HERITAGE COLOUR PALETTE



JULIET BALCONIES WITH CLEAR GLASS ON LIVING SPACE WINDOWS FACING FRANKLIN GREEN PARK & HARRIS GREEN PARK

MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8

2020-03-20 REVISED FOR REZONING
2019-10-30 REVISED FOR REZONING
2019-09-13 REVISED FOR REZONING
2019-05-15 ISSUED FOR REZONING

DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001





PEARL COLOURED ULTRA-HIGH PERFORMANCE CONCRETE PANEL



TRANSPARENT GLAZING WITH DARK GREY FRAMES



EXISTING WHITE GLAZED BRICK



EXISTING ORNAMENTAL DETAILING RESTORED TO HERITAGE COLOUR PALETTE



JULIET BALCONIES WITH CLEAR GLASS ON LIVING SPACE WINDOWS FACING FRANKLIN GREEN PARK & HARRIS GREEN PARK


MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8

2020-03-20 REVISED FOR REZONING
2019-10-30 REVISED FOR REZONING
2019-09-13 REVISED FOR REZONING
2019-05-15 ISSUED FOR REZONING

DATE REVISION DESCRIPTION


PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001




1 ENTRY GATE (CLOSED) - ELEVATION

A204 1:50




2 ENTRY GATE (OPEN) - ELEVATION

A204 1:50




5 CANOPY & SIGNAGE STUDY

A204 1:50




3 ENTRY GATE (CLOSED) - PLAN

A204 1:50




4 ENTRY GATE (OPEN) - PLAN

A204 1:50



6 WINDOW PROPORTION STUDY

A204 1:50



MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8

2020-03-20 3 REVISED FOR REZONING
2019-10-30 2 REVISED FOR REZONING
2019-09-13 1 REVISED FOR REZONING
2019-05-15 0 ISSUED FOR REZONING

DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001

A251

STREETSCAPE ELEVATIONS



PEARL COLOURED ULTRA-HIGH PERFORMANCE CONCRETE PANEL



TRANSPARENT GLAZING WITH DARK GREY FRAMES



EXISTING WHITE GLAZED BRICK



EXISTING ORNAMENTAL DETAILING RESTORED TO HERITAGE COLOUR PALETTE



JULIET BALCONIES WITH CLEAR GLASS ON LIVING SPACE WINDOWS FACING FRANKLIN GREEN PARK & HARRIS GREEN PARK


MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8


2020-03-20 REVISED FOR REZONING
2019-10-30 REVISED FOR REZONING
2019-09-13 REVISED FOR REZONING
2019-05-15 ISSUED FOR REZONING

DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001





JULIET BALCONIES WITH CLEAR GLASS ON LIVING SPACE WINDOWS FACING FRANKLIN GREEN PARK & HARRIS GREEN PARK

MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8


2020-03-20 REVISED FOR REZONING
2019-10-30 REVISED FOR REZONING
2019-09-13 REVISED FOR REZONING
2019-05-15 ISSUED FOR REZONING



DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001


A302
SECTIONS








PEARL COLOURED ULTRA-HIGH PERFORMANCE CONCRETE PANEL



TRANSPARENT GLAZING WITH DARK GREY FRAMES



EXISTING WHITE GLAZED BRICK



EXISTING ORNAMENTAL DETAILING RESTORED TO HERITAGE COLOUR PALETTE



JULIET BALCONIES WITH CLEAR GLASS ON LIVING SPACE WINDOWS FACING FRANKLIN GREEN PARK & HARRIS GREEN PARK


MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8

2020-03-20 3 REVISED FOR REZONING
2019-10-30 2 REVISED FOR REZONING
2019-09-13 1 REVISED FOR REZONING
2019-05-15 0 ISSUED FOR REZONING

DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001



1 SECTION LOOKING SOUTH THROUGH NEW 6 STOREY VOLUME

A305



1:150



2 SECTION LOOKING SOUTH THROUGH EXISTING BUILDING NEW 6 STOREY VOLUME

A305

1:150



MGA

© MGA 2016

MATERIALITY



PEARL COLOURED ULTRA-HIGH PERFORMANCE CONCRETE PANEL



TRANSPARENT GLAZING WITH DARK GREY FRAMES



EXISTING WHITE GLAZED BRICK



EXISTING ORNAMENTAL DETAILING RESTORED TO HERITAGE COLOUR PALETTE



JULIET BALCONIES WITH CLEAR GLASS ON LIVING SPACE WINDOWS FACING FRANKLIN GREEN PARK & HARRIS GREEN PARK

MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8

2020-03-20 REVISED FOR REZONING
2019-10-30 REVISED FOR REZONING
2019-09-13 REVISED FOR REZONING
2019-05-15 ISSUED FOR REZONING




DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001

A308

STREETSCAPE CROSS
SECTIONS



MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8




2020-03-20 REVISED FOR REZONING
2019-10-30 REVISED FOR REZONING
2019-09-13 REVISED FOR REZONING
2019-05-15 ISSUED FOR REZONING
DATE REVISION DESCRIPTION

PARKWAY



1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001

A800
CALCULATIONS LEGEND



MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8



2020-03-20  REVISED FOR REZONING
2019-10-30  REVISED FOR REZONING
2019-09-13  REVISED FOR REZONING
2019-05-15  ISSUED FOR REZONING


DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001



1 FSR LEVEL 1
A801 1:100

A801
FSR LEVEL 1



MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8



2020-03-20  REVISED FOR REZONING
2019-10-30  REVISED FOR REZONING
2019-09-13  REVISED FOR REZONING
2019-05-15  ISSUED FOR REZONING


DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001

1
FSR LEVEL 2
A802

A802
FSR LEVEL 2



MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8



2020-03-20 REVISED FOR REZONING
2019-10-30 REVISED FOR REZONING
2019-09-13 REVISED FOR REZONING
2019-05-15 ISSUED FOR REZONING


DATE REVISION DESCRIPTION


PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001

1 FSR LEVEL 3
A803 1:100

A803
FSR LEVEL 3







LEVEL 5										
METRIC (M ²)										
	LENGTH	WIDTH	AREA	QTY	TOTAL					
GROSS AREA										
A11	18.82	x	52.50	=	988.12 m ²					
A1	0.19	x	14.33	=	2.73 m ²					
AA1	(SEE AA CALCULATIONS)			=	0.28 m ²					
				x	1					
				=	0.28 m ²					
TOTAL GROSS AREA										
	993.86 m ²									
AREA DEDUCTIONS										
H	5.44	x	2.08	=	11.32 m ²					
Y	(SEE Y CALCULATIONS)			=	7.58 m ²					
AB1	0.06	x	16.27	=	1.03 m ²					
				x	1					
				=	1.03 m ²					
TOTAL DEDUCTIONS										
	72.83 m ²									
TOTAL GROSS AREA										
	993.86 m ²									
TOTAL DEDUCTIONS										
	72.83 m ²									
TOTAL NET AREA										
	921.02 m ²									
Y CALCULATIONS										
GROSS AREA										
Y _a	0.82	x	1.88	=	1.54 m ²					
Y _b	0.61	x	2.14	=	1.31 m ²					
Y _c	1.72	x	1.41	=	2.42 m ²					
Y _d	1.41	x	3.49	=	4.92 m ²					
	x		x	x	1					
				=	0.77 m ²					
				x	0.66 m ²					
				=	1.21 m ²					
				=	4.92 m ²					
TOTAL NET AREA										
	7.56 m ²									
Z CALCULATIONS										
GROSS AREA										
Z _a	0.82	x	1.66	=	1.36 m ²					
Z _b	0.61	x	2.10	=	1.29 m ²					
Z _c	1.68	x	1.41	=	2.37 m ²					
Z _d	1.41	x	3.54	=	4.99 m ²					
Ze	0.09	x	1.85	=	0.16 m ²					
	x		x	x	1					
				=	0.68 m ²					
				x	0.65 m ²					
				=	1.18 m ²					
				=	4.99 m ²					
				=	0.08 m ²					
TOTAL NET AREA										
	7.58 m ²									
AA CALCULATIONS										
GROSS AREA										
A _a	0.19	x	1.26	=	0.24 m ²					
A _b	0.19	x	0.37	=	0.07 m ²					
	x		x	x	1					
				=	0.34 m ²					
				x	0.04 m ²					
TOTAL NET AREA										
	0.28 m ²									

MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8



2020-03-20  REVISED FOR REZONING
2019-10-30  REVISED FOR REZONING
2019-09-13  REVISED FOR REZONING
2019-05-15  ISSUED FOR REZONING


DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001

1
FSR LEVEL 5
A805 1:100

A805
FSR LEVEL 5



MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8



2020-03-20 REVISED FOR REZONING
2019-10-30 REVISED FOR REZONING
2019-09-13 REVISED FOR REZONING
2019-05-15 ISSUED FOR REZONING

DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001

1 FSR LEVEL 6
A806 1:100

A806
FSR LEVEL 6



MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8

2020-03-20 REVISED FOR REZONING
2019-10-30 REVISED FOR REZONING
2019-09-13 REVISED FOR REZONING
2019-05-15 ISSUED FOR REZONING

DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001

1

VIEW NORTHWEST FROM CORNER OF PANDORA & COOK
A811



MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8

2020-03-20 REVISED FOR REZONING
2019-10-30 REVISED FOR REZONING
2019-09-13 REVISED FOR REZONING
2019-05-15 ISSUED FOR REZONING


DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001

1 **VIEW WEST THROUGH RESIDENTIAL MEWS**
A812

A812
3D RENDERS



MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8

2020-03-20	 3	REVISED FOR REZONING
2019-10-30	 2	REVISED FOR REZONING
2019-09-13	 1	REVISED FOR REZONING
2019-05-15	 0	ISSUED FOR REZONING

DATE REVISION DESCRIPTION

PARKWAY


1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001

1

VIEW SOUTHWEST FROM COOK STREET

A813

A813
3D RENDERS



MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8

2020-03-20 REVISED FOR REZONING
2019-10-30 REVISED FOR REZONING
2019-09-13 REVISED FOR REZONING
2019-05-15 ISSUED FOR REZONING

DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001

1 **VIEW EAST TO COURTYARD**
A815

A814
3D RENDERS



MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8

2020-03-20 3 REVISED FOR REZONING
2019-10-30 2 REVISED FOR REZONING
2019-09-13 1 REVISED FOR REZONING
2019-05-15 0 ISSUED FOR REZONING

DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001

1 BALCONY STUDY
A816

A815
3D RENDERS



1 ADJACENT PROPERTY STUDY | VIEW WEST ACROSS COOK STREET
A817



3 ADJACENT PROPERTY STUDY | VIEW EAST ACROSS FRANKLIN GREEN PARK
A817






2 ADJACENT PROPERTY STUDY | VIEW SOUTHWEST DOWN COOK STREET
A817



4 ADJACENT PROPERTY STUDY | VIEW WEST ALONG NORTH WALKWAY
A817

MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8


2020-03-20  REVISED FOR REZONING
2019-10-30  REVISED FOR REZONING
2019-09-13  REVISED FOR REZONING
2019-05-15  ISSUED FOR REZONING

DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001

A817
ADJACENT PROPERTY
STUDY



MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8




2020-03-20 REVISED FOR REZONING
2019-10-30 REVISED FOR REZONING
2019-09-13 REVISED FOR REZONING
2019-05-15 ISSUED FOR REZONING


DATE REVISION DESCRIPTION

PARKWAY


1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001




1 LEVEL 2, 9:00 AM, 14.50 (LUX)
A822




3 LEVEL 3, 9:00 AM, 24.67 (LUX)
A822




5 LEVEL 4, 9:00 AM, 34.83 (LUX)
A822




2 LEVEL 2, 3:00 PM, 14.50 (LUX)
A822



4 LEVEL 3, 3:00 PM, 24.67 (LUX)
A822



6 LEVEL 4, 3:00 PM, 34.83 (LUX)
A822



MICHAEL GREEN ARCHITECTURE
1535 W 3RD AVENUE, VANCOUVER BC
CANADA V6J 1J8




2020-03-20 REVISED FOR REZONING
2019-10-30 REVISED FOR REZONING
2019-09-13 REVISED FOR REZONING
2019-05-15 ISSUED FOR REZONING

DATE REVISION DESCRIPTION

PARKWAY

1050 PANDORA AVE + 1518 COOK STREET
VICTORIA, BC
2018-001

SEAL:



NO.	DATE	REVISION DESCRIPTION	DR.
10	20.MAR.13	REV. PER COV COMMENTS	BA
9	19.NOV.28	100% BP SET	BA
8	19.NOV.04	90% CD SET	BA
7	19.OCT.23	NEW GROUND FLOOR PLAN	DD
6	19.OCT.22	REVISION	DD
5	19.OCT.21	NEW SITE PLAN/CLIENT REQUEST	DD
3	19.OCT.03	60% CD SET	BA
2	19.SEP.27	REZONING	BA
1	21.AUG.19	REV. PER CITY/CLIENT COMMENTS	BA
-	19.JUL.29	30% BP SUBMISSION	BA

CLIENT:

PROJECT:

**PARKWAY
MIXED USE DEVELOPMENT**

**1050 PANDORA AVENUE
VICTORIA, BC**

**DRAWING TITLE:
LANDSCAPE
PLAN**


DATE: 19.JUL.10 DRAWING NUMBER:
SCALE: 1:100
DRAWN: BA
DESIGN: BA
CHK'D: OF 9

L1

OF 9

PMG PROJECT NUMBER:

18240-11.ZIP 18240





NO.	DATE	REVISION DESCRIPTION	DR.
10	20.MAR.13	REV. PER COV COMMENTS	BA
9	19.NOV.28	100% BP SET	BA
8	19.NOV.04	90% CD SET	BA
7	19.OCT.23	NEW GROUND FLOOR PLAN	DD
6	19.OCT.22	REVISION	DD
5	19.OCT.21	NEW SITE PLAN&CLIENT REQUEST	DD
3	19.OCT.03	60% CD SET	BA
2	19.SEP.27	REZONING	BA
1	21.AUG.19	REV. PER CITY/CLIENT COMMENTS	BA
-	19.JUL.29	30% BP SUBMISSION	BA

CLIENT:

PROJECT:

**PARKWAY
MIXED USE DEVELOPMENT**

**1050 PANDORA AVENUE
VICTORIA, BC**


DRAWING TITLE:
**SHRUB
PLAN**

DATE: 19.JUL.10 DRAWING NUMBER:
SCALE: 1:100
DRAWN: BA
DESIGN: BA
CHK'D: BA
OF 9


L2

PMG PROJECT NUMBER:

18240-11.ZIP 18240



SEAL:



NO.	DATE	REVISION DESCRIPTION	DR.
10	20.MAR.13	REV. PER COV COMMENTS	BA
9	19.NOV.28	100% BP SET	BA
8	19.NOV.04	90% CD SET	BA
7	19.OCT.23	NEW GROUND FLOOR PLAN	DD
6	19.OCT.22	REVISION	DD
5	19.OCT.21	NEW SITE PLAN&CLIENT REQUEST	DD
3	19.OCT.03	60% CD SET	BA
2	19.SEP.27	REZONING	BA
1	21.AUG.19	REV. PER CITY/CLIENT COMMENTS	BA
-	19.JUL.29	30% BP SUBMISSION	BA

CLIENT:

PROJECT:

PARKWAY
MIXED USE DEVELOPMENT


1050 PANDORA AVENUE
VICTORIA, BC

DRAWING TITLE:

LEVEL 3
ROOF LANDSCAPE


DATE: 19.JUL.10 DRAWING NUMBER:
SCALE: 1:100
DRAWN: BA
DESIGN: BA
CHKD: OF 9

SEAL:



PLANT SCHEDULE				PMG PROJECT NUMBER: 18-240
KEY	QTY	BOTANICAL NAME	COMMON NAME	PLANTED SIZE / REMARKS
GRASS	79	CALAMAGROSTIS BRACHYTRICHA	KOREAN FEATHER REED GRASS	#1 POT

NOTES: * PLANT SIZES IN THIS LIST ARE SPECIFIED ACCORDING TO THE BC LANDSCAPE STANDARD AND CANADIAN LANDSCAPE STANDARD, LATEST EDITION. CONTAINER SIZES SPECIFIED AS PER CNLA STANDARD. BOTH PLANT SIZE AND CONTAINER SIZE ARE THE MINIMUM ACCEPTABLE SIZES. * REFER TO SPECIFICATIONS FOR DEFINED CONTAINER MEASUREMENTS AND OTHER PLANT MATERIAL REQUIREMENTS. * SEARCH AND REVIEW: MAKE PLANT MATERIAL AVAILABLE FOR OPTIONAL REVIEW BY LANDSCAPE ARCHITECT AT SOURCE OF SUPPLY. ARDUOUS SEARCHES FOR LOWER PRICED PLANT MATERIAL IN OTHER AREAS ARE NOT ALLOWED. * PLANT MATERIAL PROVIDED BY LANDSCAPE ARCHITECT PRIOR TO PLANTING ANY SUBJECTS RELATED TO THE SPECIFIED MATERIAL. UNAPPROVED PLANT SUBSTITUTIONS WILL BE REJECTED. ALLOW A MINIMUM OF FIVE DAYS PRIOR TO DELIVERY FOR REQUEST TO SUBSTITUTE. SUBSTITUTIONS ARE SUBJECT TO BC LANDSCAPE STANDARD AND CANADIAN LANDSCAPE STANDARD LATEST EDITION. * ALL PLANT MATERIAL MUST BE PROVIDED FROM CERTIFIED DISEASE FREE NURSERY. * BIO-SOLIDS NOT PERMITTED IN GROWING MEDIUM UNLESS AUTHORIZED BY LANDSCAPE ARCHITECT.



10	20.MAR.13	REV. PER COV COMMENTS	BA
9	19.NOV.28	100% BP SET	BA
8	19.NOV.04	90% CD SET	BA
7	19.OCT.23	NEW GROUND FLOOR PLAN	DD
6	19.OCT.22	REVISION	DD
5	19.OCT.21	NEW SITE PLAN&CLIENT REQUEST	DD
3	19.OCT.03	60% CD SET	BA
2	19.SEP.27	REZONING	BA
1	21.AUG.19	REV. PER CITY/CLIENT COMMENTS	BA
-	19.JUL.29	30% BP SUBMISSION	BA

NO. DATE REVISION DESCRIPTION DR.

CLIENT:

PROJECT:

PARKWAY
MIXED USE DEVELOPMENT







1050 PANDORA AVENUE
VICTORIA, BC

DRAWING TITLE:

**LEVEL 5
ROOF LANDSCAPE**

DATE: 19.JUL.10 DRAWING NUMBER:
SCALE: 1:100
DRAWN: BA
DESIGN: BA
CHKD: OF 9

L5



NO.	DATE	REVISION DESCRIPTION	DR.
10	20.MAR.13	REV. PER COV COMMENTS	BA
9	19.NOV.28	100% BP SET	BA
8	19.NOV.04	90% CD SET	BA
7	19.OCT.23	NEW GROUND FLOOR PLAN	DD
6	19.OCT.22	REVISION	DD
5	19.OCT.21	NEW SITE PLAN&CLIENT REQUEST	DD
3	19.OCT.03	60% CD SET	BA
2	19.SEP.27	REZONING	BA
1	21.AUG.19	REV. PER CITY/CLIENT COMMENTS	BA
-	19.JUL.29	30% BP SUBMISSION	BA

CLIENT:

PARKWAY
MIXED USE DEVELOPMENT

1050 PANDORA AVENUE
VICTORIA, BC

DRAWING TITLE:

**LANDSCAPE
DETAILS AND SECTIONS**



DATE: 19.JUL.10 DRAWING NUMBER:
SCALE: AS SHOWN
DRAWN: BA
DESIGN: BA
CHKD: BA
OF 9

L6

SEAL:



LIGHTING LEGEND	
KEY	DESCRIPTION
◇	SINGLE GLOBE PEDESTRIAN LIGHT PHILLIPS MICENAS LED4 OR APPROVED EQUIVALENT BDP791 LED43-4S/740 II DS50 GF BK 76
▲	SINGLE GLOBE PEDESTRIAN LIGHT PHILLIPS MICENAS LED4 OR APPROVED EQUIVALENT BDP791 LED43-4S/740 II DS50 GF BK 76
---	SINGLE GLOBE PEDESTRIAN LIGHT PHILLIPS MICENAS LED4 OR APPROVED EQUIVALENT BDP791 LED43-4S/740 II DS50 GF BK 76



10	20.MAR.13	REV. PER COV COMMENTS	BA
9	19.NOV.28	100% BP SET	BA
8	19.NOV.04	90% CD SET	BA
7	19.OCT.23	NEW GROUND FLOOR PLAN	DD
6	19.OCT.22	REVISION	DD
5	19.OCT.21	NEW SITE PLAN&CLIENT REQUEST	DD
3	19.OCT.03	60% CD SET	BA
2	19.SEP.27	REZONING	BA
1	21.AUG.19	REV. PER CITY/CLIENT COMMENTS	BA
-	19.JUL.29	30% BP SUBMISSION	BA
NO.	DATE	REVISION DESCRIPTION	DR.

CLIENT:

PROJECT:

PARKWAY
MIXED USE DEVELOPMENT

1050 PANDORA AVENUE
VICTORIA, BC

DRAWING TITLE:

**LIGHTING
LAYOUT PLAN**

DATE: 19.JUL.10 DRAWING NUMBER:
SCALE: 1:100
DRAWN: BA
DESIGN: BA
CHK'D: BA

L7

OF 9

PART ONE GENERAL REQUIREMENTS	
11 REFERENCE	
1.1 CDOC 2008 Comply with all articles in the General Conditions of Contract in conjunction with this section unless superseded by other Contract Documents.	
1.2 Canadian Landscape Standard, latest edition, prepared by the Canadian Society of Landscape Architects and the Canadian Landscape & Nursery Association, jointly. All work and materials shall meet standards as set out in the Canadian Landscape Standard unless superseded by this specification or as directed by Landscape Architect with written instruction.	
1.3 MASTER MUNICIPAL SPECIFICATIONS & STANDARD DETAILS, 2000 edition, prepared by the Consulting Engineers of British Columbia, Roadbuilders and Heavy Construction Association, and the Municipal Engineers Division.	
1.4 STANDARD FOR LANDSCAPE IRRIGATION SYSTEM, 2008 Prepared by the Irrigation Industry Association of British Columbia.	
1.5 MUNICIPAL BYLAWS AND ENGINEERING SPECIFICATIONS WHERE NOTED.	
1.6 TE 1. A current (not more than one month) test for all growing medium to be used on this site is required. Provide and pay for testing by an independent testing facility pre-approved by the Landscape Architect. Deliver growing medium test results to Landscape Architect for review and approval prior to placement. Refer to Section 3.4 Growing Medium Testing for procedure.	
1.7 Owner reserves the right to test or re-test materials. Contractor responsible to pay for testing if materials do not meet specification.	
1.8 SUBMITTALS 1. Any alternate products differing from that contained in the contract documents must be pre-approved by the Landscape Architect.	
2. Submittals to consist of product sample or manufacturer's product description.	
1.9 SITE REVIEW 1. Under the terms of the Landscape Architect's Contract with the Owner and where the Landscape Architect is the designated reviewer, the Landscape Architect will observe construction as it is necessary in their opinion to confirm conformance to the plans and specifications. Contact Owner's Representative to arrange for site observation at the appropriate times. After two days notice, Observation schedule may include but will not be limited to the following: 1.1 Start of Work - General Contract: Prior to any site disturbance, a meeting with the general contractor to review tree preservation issues, general landscape issues and municipal requirements. 1.2 Start to Site Meeting, Landscape Contract (if separate): At the start of work with Owner's Representative, Site Superintendent and Landscape Contractor; a meeting is to be held to review expected work and to verify the acceptability of the subgrade and general site conditions to the Landscape Contractor. Provide growing medium test results for review. 1.3 Progress Site Visit: To observe materials and workmanship as necessary throughout the course of the work. Review different aspects of the work as may be dealt with on any single visit. Such elements may include Site Layout, Rough Grading, Growing Medium - quality, depths, finish grading, Drainage and Irrigation Materials, Lawns or Grass areas, Planting - plant material including negotiations with suppliers, nursery inspections, plant sizes, quality, quantity, planting practice, layout, free support, Mulch, Irrigation Systems, Planting - plant material including negotiations with suppliers, nursery inspections, plant sizes, quality, quantity, planting practice, layout, free support; Fertilizer, structural walls and slabs, Tint Paint.	
1.4 Substantial Performance: Review of all work, accounting of all substitutions, deletions, plant counts, preparations of deficiency list, and recommendations for completion.	
1.5 Certificate of Completion: Upon the declaration of Substantial Performance, a recommendation for the issuance of the Certificate of Completion will be made to the Payment Certifier as defined in the contract.	
1.6 Deficiency Review: Prior to the completion of the holdback period, check for completion of deficiencies. Once completed, a Schedule 'C' will be issued where required.	
1.7 Warranty Review: Prior to the completion of the warranty period (+/- 11 months after issuance of the Certificate of Completion), review all warranty material and report recommendations for warranty replacement.	
1.8 NORMANSHIPS	
1. Unless otherwise instructed in the Contract Documents, the preparation of the subgrade shall be the responsibility of the General Contractor. Placement of growing medium constitutes acceptance of the subgrade by the Landscape Contractor. Any subsequent corrections to the subgrade require are the responsibility of the Landscape Contractor.	
2. All work and superintendence shall be performed by personnel skilled in landscape contracting. In addition, all personnel applying herbicides and/or pesticides shall hold a current license issued by the appropriate authorities.	
3. A site visit is required to become familiar with site conditions before bidding and before start of work.	
4. Confirm location of all services before proceeding with any work.	
5. Notify Landscape Architect of any discrepancies. Obtain approval from Landscape Architect prior to departing from the plans.	
6. Take appropriate measures to avoid environmental damage. Do not dump any waste materials into water bodies. Conform with all federal, provincial and local statutes and guidelines.	
7. Collect and dispose of all debris and/or excess material from landscape operations. Keep paved surfaces clean and repair damage resulting from landscape work. Repairs are to be completed prior to final acceptance.	
8. Where new work connects with existing, and where existing work is altered, make good to match existing undisturbed condition.	
1.6 WARRANTIES	
1.1 Guarantee all materials and workmanship for a minimum period of one full year from the date of Certificate of Completion.	
1.2 Refer to individual sections for specific warranties.	
PART TWO SCOPE OF WORK	
2.1 SCOPE OF WORK	
1. Other conditions of Contract may apply. Confirm Scope of Work at time of tender.	
2. Work includes supply of all related items and performing all operations necessary to complete the work in accordance with the drawings and specifications and generally consists of the following:	
2.1 Retention of Existing Trees where shown on drawings.	
2.2 Finish Grading and Landscape Drainage.	
2.3 Supply and placement of growing medium.	
2.4 Testing and prepared growing medium for on-site topsoil.	
2.5 Preparation and incorporation of additives to meet requirements of soil test and Table One.	
2.6 Preparation of planting beds, supply of plant material and planting.	
2.7 Preparation of rough grass areas, supply of materials and seeding.	
2.8 Preparation of areas, supply of materials and sodding.	
2.9 Irrigation and drainage.	
2.10 Maintenance of planted and seeded/sodded areas until accepted by Owner.	
2.11 SEPARATE PRICE Establishment Maintenance, Section 3.11.	
2.12 Other work other than this list, not specified by Landscape Architect.	
2.2 MATERIALS	
1. Growing Medium: Conform to Canadian Landscape Standard for definitions of imported and on-site topsoil. Refer to Table One below.	
TABLE ONE PROPERTIES OF GROWING MEDIUM FOR LEVEL 2 GROWDED AND LEVEL 1 MODERATE AREAS Canadian System of Soil Classification Textural Class: "Loamy Sand" to "Sandy Loam"	
Applications	
Low Traffic Areas, Trees and Large Shrubs	
High Traffic Areas, Lawns and Planters	
Growing Medium Types	
2L	
2H	
2P	
Texture	
Percent of Dry Weight of Total Growing Medium	
Coarse Gravel: larger than 25mm	
0 - 1%	
All Gravel: larger than 2mm	
0 - 5%	
0 - 5%	
Percent of Dry Weight of Growing Medium Excluding Gravel	
Sand: larger than 0.05mm smaller than 2mm	
50 - 80%	
70 - 90%	
40 - 80%	
Silt: larger than 0.002mm smaller than 0.05mm	
10 - 25%	
0 - 15%	
10 - 25%	
Clay: smaller than 0.002mm	
0 - 25%	
0 - 15%	
0 - 25%	
Clay and Silt Combined	
maximum 35%	
maximum 15%	
maximum 35%	
Organic Content (coast):	
3 - 10%	
3 - 5%	
10 - 20%	
Organic Content (interior):	
3 - 5%	
15 - 20%	
Ashity (pH):	
6.0 - 7.0	
6.0 - 7.0	
4.5 - 6.5	
Drainage:	
Percolation shall be such that no standing water is visible 60 minutes after at least 10 minutes of moderate to heavy rain or irrigation.	
2. Fertilizer: An organic and/or inorganic compound containing Nitrogen (N), Phosphate (P), and Potash (K) and Potash (K) in proportions required by soil test.	
3. Lime: Ground agricultural limestone. Meet requirements of the Canadian Landscape Standard.	
4. Organic Additive: Commercial compost product to the requirements of the Canadian Landscape Standard, latest edition and pre-approved by the Landscape Architect. Recommended suppliers: The Answer Garden Products, Fraser Richards Sols & Fibre, Stream Organics Management.	
5. Sand: Clean, washed sand to meet requirements of the Canadian Landscape Standard.	
6. Composted Bark Mulch: 50mm (3/8") minus Fir/Hemlock bark chips and fines, free of chunks and sticks, dark brown in colour and free of all soil, stones, roots or other extraneous matter. Fresh orange in colour will be rejected.	
7. Herbicides and Pesticides: If used, must conform to all federal, provincial and local statutes. Appliers must hold current licenses issued by the appropriate authorities in the area.	
8. Filter Fabric: A non biodegradable blanket or other filtering membrane that will allow the passage of water but not fine soil particles. (Such as MIRAFI 10 NL, GEOLON N40 OR AMCO 4545 or alternate product pre-approved by the Landscape Architect.)	
9. Drainage Pipe: If required, Schedule 40 PVC nominal size.	
10. Drain Rock: Clean, round, inert, durable, and have a maximum size of 19mm and containing no material smaller than 10mm.	
11. Plant Material: To the requirements of the Canadian Landscape Standard. Refer to 3.9, Plants and Planting. All plant material must be provided from a certified disease free nursery. Provide proof of certification.	
12. Sod: Refer to individual sections in this specification.	
13. Supplier and installers of segmental block walls to provide engineered drawings for all walls; signed and sealed drawings for all walls, individually, in excess of 12m, or combinations of walls collectively in excess of 12m. Installations must be reviewed and signed off by Certified Professional Engineer; include cost of engineering services in Tender price.	
14. Miscellaneous: Any other material necessary to complete the project as shown on the drawings and described herein.	

PART THREE SOFT LANDSCAPE DEVELOPMENT			
3.1 RETENTION OF 1. Prior to any work on site - protect individual trees or plant groupings indicated as retained on landscape plans as vegetation retention areas. 1.1 In some instances the Landscape Architect will flag trees or areas. Discuss tree retention areas at a start-up meeting with the Landscape Architect.			
2. A physical barrier must be installed to delineate clearing boundaries. Refer to physical barrier detail. If detail not provided, comply with local municipal requirements.			
3. No machine travel through or within vegetation retention areas or under crowns of trees to be retained is allowed.			
4. Do not stockpile soil, construction materials, or excavated materials within vegetation retention areas.			
5. Do not park, fuel or service vehicles within vegetation retention areas.			
6. No debris fires, cleaning fires or trash burning shall be permitted within vegetation retention areas.			
7. No excavations, drain or service trenches nor any other disruption shall be permitted within vegetation retention areas without a review of the proposed encroachment by the Landscape Architect.			
8. Do not cut branches or roots of retained trees without the approval of the Landscape Architect.			
9. Any damage to existing vegetation intended for preservation will be subject to evaluation by an I.S.A. Certified Arborist using the "Guide for Plant Appraisal", Eighth Edition, 1992.			
10. In municipalities with specific tree retention bylaws ensure compliance to bylaws.			
11. In situations where required construction may disturb existing vegetation intended for preservation, contact Landscape Architect for review prior to commencing construction.			
3.2 GRADES 1. Ensure subgrade is prepared to depths specified in Section 3.5, Growing Medium, below. Where planting is indicated close to existing trees, prepare suitable planting pockets for material indicated on the planting plan. Shape subgrade to eliminate free standing water and conform to the site grading and drainage plan.			
2. On slopes in excess of 3:1 trench subgrade across slope to 150mm (6") minimum at 15m (5 ft) intervals.			
3. Scarsy the entire subgrade immediately prior to placing growing medium. Re-cultivate where vehicular traffic results in compaction during the construction procedures. Ensure that all planting areas are smoothly contoured after light compaction to finished grades.			
4. Eliminate standing water from finished grades. Provide a smooth, firm and even surface and conform to grades shown on the Landscape Drawings. Do not exceed maximum and minimum gradients defined by the Canadian Landscape Standard.			
5. Construct swales true to grade and grade, smooth and free of sags or high points. Minimum slope 2%, maximum side slopes 10%. Ensure positive drainage to collection points.			
6. Slope not to exceed the following: Rough 3:1, Sawn 3:1, Lawn 2:1, Landscape plantings 2:1.			
7. Finished soil/mulch elevation at building to comply with municipal requirements.			
8. Inform Landscape Architect of completion of finish grade prior to placement of seed, sod, plants or mulch.			
3.3 LANDSCAPE SODDING 1. Related Work: Growing medium and Finish Grading, Grass areas, Trees Shrubs and Groundcovers, Planters, Crib Walls.			
2. Work Included: Site finish grading and surface drainage. Installation of any drainage systems detailed on landscape plans. Note: Catch basins shown on landscape plans for coordination only, confirm scope of work prior to bid.			
3. General: Treat all areas defined as lawn areas on the landscape plan between all property lines of the project including all boulevards to edge of roads and lanes.			
4. Growing Medium: Comply with Section 2.21, Growing Medium. Prior to sodding, request an inspection of the finished grade, and depth and condition of growing medium by the Landscape Architect.			
5. Time of Sodding: Sod from April 1st to October 1st. Further extensions may be obtained on concurrence of the Landscape Architect.			
6. Sodding: Sod supply to all conditions of Canadian Landscape Standard, Section 8, B.C. Standard for Turfgrass Sod.			
7. Sodding: Sodding by area. Refer to Table 2 below.			
TABLE 2 SPECIFIED TURFGRASS BY AREA			
Ar	Description	Quality Grade	Major Species
CLASS 1	Lawn, all areas noted on drawings as lawn in urban development sites including bounded grass	No 1 Premium	Kentucky Blue grass, Fescues for shade
CLASS 2	Grass - public parks, industrial and institutional sites	No 2 Standard	
CLASS 3	Rough Grass	see hydroseeding	sz
SPECIAL			
8. Application Rate: 8.1 Seed Mixture: 136 kg/ha (172 lbs/acre) 8.2 Fertilizer: 112 kg/ha (140 lbs/acre) 8.3 Coarse Wildflower Mix: Where specified, apply 31 lbs/acre (3/4 lb. 1 lb. of grass seed)			
8.4 Notes: 8.4.1 At the time of tender provide a complete chart of all components of the mix proposed including mulch, fertilizer, water etc. Sloped sites require fertilizer. 8.4.2 Fertilizer. 8.4.3 Rough Grass: If a soil analysis is available, comply with soil analysis results.			

PART ONE - GENERAL	
1.1 COP 1. The Structural Soil specification is provided as an instrument of service and remains the property of PMG Landscape Architects. The information provided in this specification is for exclusive use by our client for the specific project noted. This information contained in this document may not be reproduced or distributed, in whole or in part, without the permission of PMG Landscape Architects.	
1.2 SCOPE 1. The work of this section shall govern the supply of all equipment, materials and labour necessary for the preparing and placing and compacting Structural Soil Mix on a prepared sub grade. 2. It is the intent that the structural soil mixture will provide the necessary load bearing characteristics for light load hard surface paving areas while allowing and promoting the development of tree roots. The long term goals the promotion of healthy, long lived trees while reducing the potential negative implications of large scale root development under hard surface areas. 3. Refer to drawings for location and dimension of structural soil mixture. 4. All other related work as described in the drawings and/or this specification.	
1.3 RELATED WORK 1. Section 02100, Landscape Requirements 2. Section 02710, Landscape Drainage 3. Section 02810, Irrigation System 4. Section 02933, Sodding [Seeding] 5. Section 02906, Planting Trees, Shrubs, and Groundcover	
1.4 RELATED MASTER MUNICIPAL SPECIFICATIONS 1. Contractor to report all conflicts with civil engineering to Landscape Architect 2. Section 02210, Site Grading 3. Section 02223, Excavating, Trenching, and Backfilling 4. Section 02226, Aggregates and Granular Materials 5. Section 02227, Waterworks 6. Section 02721, Storm Sewers 7. Section 02725, Manholes and Catch Basins	
1.5 STANDARDS 1. BCSLA/BCLNA Landscape Standard (most current edition) 2. Canadian System of Soil Classification	
1.6 QUALITY ASSURANCE 1. All structural soil material used in street tree planting shall be from a source approved by the Consultant and all similar materials supplied to the site shall be of similar nature and from a single source. 14 days prior to supplying any material to the site, inform the Consultant of proposed source and provide a copy of an analysis undertaken by a recognized testing agency approved by the owner, at the Contractor's expense and indicating the particle size characteristics of the proposed material in written form as laid out in 2.1 of this section. 2. All nutritive admixtures to structural soil material supplied to the site shall be from a source approved by the Consultant and all similar nutritive admixtures supplied to the site shall be of similar nature and from a single source. 14 days prior to supplying any nutritive admixture, inform the Consultant of proposed source and provide a copy of an analysis undertaken by a recognized testing agency approved by the owner. The test report shall quantify and qualify the following characteristics of the proposed nutritive admixture: - Gravel, sand and fines content each as a % of dry weight mineral - Organic material content as a percentage of dry weight - Acidity (pH) - Salinity in millihm/cm at 25 degrees C. - Basic fertility (total nitrogen available K, N, Mg, P) - Recommendation for incorporation of necessary amendments. 3. Provide and pay for all required testing of materials proposed for use on this project. At the Consultant's discretion, all materials may be re-tested. Contractor will be responsible for costs of re-testing if materials do not meet specification and for correction of the deficiency. 4. Cost of imported materials shall include cost of modifications from source to ensure that these materials meet specifications. 5. Acceptance of material at source does not preclude future rejection if material fails to conform to requirements specified. 6. Confirm compaction of subgrade and structural soil by Geotechnical Reports from qualified Geotechnical Engineer. 7. Aggregate Test: - Provide source and sieve designation of intended aggregate material prior to ordering. - All the Landscape Architect's discretion, materials may be retested. Contractor is responsible for costs of testing if sample does not meet specification and for correction of any deficiency. - Submit 25kk sample of stone to Landscape Architect prior to mixing. Sample should be labelled to include source of material submitted. 8. Structural Soil Mix Design 8.1 Prepare sample of structural soil mix with proposed mix ratios for approval by Landscape Architect a minimum of 14 days prior to placement. Notify Landscape Architect minimum 2 days prior to mixing samples. 8.2 Landscape Architect's may request additional samples of Structural Soil mixture to be tested in the event that further refinement of the mixture is necessary.	
1.7 SCHEDULING 1. Obtain approval from Consultant of schedule 14 days in advance of structural soil preparation or delivery of material to site. Co-ordination of the installation of the structural soil mixture is critical. Ensure scheduling has been co-ordinated with all consultants and related contractors. 2. Schedule to include: 2.1 date for commencement of preparation of structural soil at source 2.2 sub grade preparation at site 2.3 shipping dates 2.4 arrival dates on site 2.5 installation dates 3. Schedule work to co-ordinate with installation of any drainage, irrigation, tree grate footings, lighting, paving etc. 4. Complete work to ensure tree planting will occur under optimum conditions 5. Do not handle or place structural soil mix in rain.	
1.8 FIELD REVIEW 1. Start up meeting with Consultant is required to confirm the areas of installation and mixing. If not previously submitted, ensure growing medium sample and test report, aggregate stone sample and structural soil sample and report are supplied at the Start-up Meeting. 2. Co-ordinate site meeting with Consultant at the following times 2.1 drainage installation and connection 2.2 irrigation installation 2.3 mixing of structural soil mixture 2.4 installation of structural soil mixture 2.5 sub grade preparation and layout 2.6 installation of trees 3. Where materials are installed in phases, it is the contractors responsibility to inform the Consultant of critical installation times for each phase as noted in Section 18.2.	
1.9 SAMPLES 1. Provide 2 kg samples of all materials required for the preparation of structural soil minimum 14 days prior to commencement of installation. Samples of all material shall be submitted with test report from approved testing agency as per section 13.2 and 13.3	
1.10 PRODUCT HANDLING 1. All materials used in the composition of structural soil shall not be prepared, worked or traveled upon when in a wet or frozen condition. 2. Supply and handle dolomite lime, fertilizer, stabilizer and other chemical amendments in standard, sealed, waterproof containers with net weight and product analysis clearly marked on exterior of package	
1.11 DELIVERY, STORAGE AND PROTECTION 1. For structural soil prepared at source and delivered to site, deliver all materials to site in such a manner as to prevent damage to or separation of all materials used in the preparation of structural soil. 2. On-site storage of prepared structural soil shall be undertaken in such a manner as to prevent damage or separation of any materials. 3. Structural soils to be installed as soon as practicable after mixing, any structural soils stored overnight whether on-site or at source shall be covered with tarpaulin of material approved by the Consultant until such time as materials installed. 4. All material to be stockpiled shall be protected in accordance with B.C. Ministry of Environment guidelines.	

PART TWO - PRODUCTS											
2.1 GROWI 1. TABLE ONE: 1.1 Provide all growing medium required to complete the work. 1.2 Comply with the requirements of Table 1, below. 1.3 Organic material in the growing medium must be well decomposed to prevent oxygen consumption caused as a result of decomposition of the organic matter in the soil mixture.											
TABL PROPE TEXTURE: Particle size classes by the Canadian System of Soil Classification											
<table border="1"> <thead> <tr> <th>Gravel: greater than 2mm - less than 75mm</th> <th>1</th> </tr> </thead> <tbody> <tr> <td>Sand: greater than 0.05mm - less than 2mm</td> <td>maximum</td> </tr> <tr> <td>Silt: greater than 0.002mm - less than 0.05 mm</td> <td>maximum</td> </tr> <tr> <td>Clay: less than 0.002mm</td> <td>maximum 15%</td> </tr> <tr> <td>Clay and Silt Combined</td> <td>maximum 40%</td> </tr> </tbody> </table>		Gravel: greater than 2mm - less than 75mm	1	Sand: greater than 0.05mm - less than 2mm	maximum	Silt: greater than 0.002mm - less than 0.05 mm	maximum	Clay: less than 0.002mm	maximum 15%	Clay and Silt Combined	maximum 40%
Gravel: greater than 2mm - less than 75mm	1										
Sand: greater than 0.05mm - less than 2mm	maximum										
Silt: greater than 0.002mm - less than 0.05 mm	maximum										
Clay: less than 0.002mm	maximum 15%										
Clay and Silt Combined	maximum 40%										
ACIDITY (pH): DRAGAGE: Minimum saturated hydraulic conductivity (cm/hr) in place. SALINITY: Saturated extract conductivity shall not exceed ORGANIC CONTENT: Percent of Dry Weight (%)											
<table border="1"> <thead> <tr> <th>DRAGAGE: Minimum saturated hydraulic conductivity (cm/hr) in place.</th> <th>3.1</th> </tr> </thead> <tbody> <tr> <td>SALINITY: Saturated extract conductivity shall not exceed</td> <td>3.0 millihm/cm at 25°C</td> </tr> <tr> <td>ORGANIC CONTENT: Percent of Dry Weight (%)</td> <td>8% - 12%</td> </tr> </tbody> </table>		DRAGAGE: Minimum saturated hydraulic conductivity (cm/hr) in place.	3.1	SALINITY: Saturated extract conductivity shall not exceed	3.0 millihm/cm at 25°C	ORGANIC CONTENT: Percent of Dry Weight (%)	8% - 12%				
DRAGAGE: Minimum saturated hydraulic conductivity (cm/hr) in place.	3.1										
SALINITY: Saturated extract conductivity shall not exceed	3.0 millihm/cm at 25°C										
ORGANIC CONTENT: Percent of Dry Weight (%)	8% - 12%										
2.2 AGGREGATE 1. Clean inert stone of high angularity is preferred over washed gravel. 2. Stone dimension aspect ratio should approach 1:1 with a maximum of 2:1 length: width: depth. 3. Single size stone, 75mm clear sieve designation: Blasted Quarry Rock. 4. Aggregate to be used for structural soil shall be free of any foreign elements or material. Provide samples and test reports as described in section 1.5 and 1.8. 5. Aggregate quality: Material shall be sound hard, durable, free from soft, thin, elongated or laminated particles, organic material, clay lumps or material, or other substances that would act in a deleterious manner or use intended.											
2.3 SOIL STABILIZER 1. A non-toxic organic binder. Product: Stabilizer, The Original Natural Binder, as available from Veratec, Aldergrove, BC 604-607-3002 (Or approved equal)											
2.4 GRANULAR BASE 1. To Master Municipal Specification Section 02226, Aggregates and Granular Materials.											
2.5 PAVING MATERIALS 1. Refer to architectural drawings.											
2.6 FILTER FABRIC 1. Non Woven filter fabric shall be installed as a separation layer directly above the compacted structural soil mixture. Do not install fabric until adequate compaction of the structural soil mixture has been confirmed. 2. Filter fabric shall be selected and designed to withstand wear and tear during construction without deterioration of its strength and filtering properties. Conform to the following ASTM designations: - Grab Tensile Strength ASTM-D-4632 400 kN - Tensile Elongation ASTM-D-4632 50% - Mullen Burst ASTM-D-4786 1270 kPa - Flow Rate ASTM-D-1491 610 l/min/m ² 3. Fabric shall be Amoco 4545 or approved equivalent.											
2.7 TREE PLANTING 1. Remove structural soil or other backfill material (sand, see comments in section 3.7.7) from the full dimensions of the tree grate area (12m x 12m x depth of root ball). 2. Re compact all material below root ball to original specified density to prevent settling of the root ball in the hole. 3. Ensure tree is planted in the exact centre of the specified planting station straight and true. 4. Install tree in accordance with BCSLA Landscape Standard. Cut away synthetic root ball twine, cut back improperly sized wire baskets, pull back burlap from around trunk etc. 5. Backfill with Growing Medium as per Section 2.1. Ensure the same growing medium used in the structural soil mix is installed as backfill material. 6. Place 50mm depth composted fir/hem bark mulch over the top of the open tree pit area.											
2.8 TREE GRATES 1. Site Furniture and to contract drawings for tree grates, frames and footings.											
2.9 ACCEPTANCE 1. Consultant shall inspect structural soil "in place" and determine acceptance of material, and finish grading prior to paving. 2. Finish grade shall be to within 15mm of proposed grades within 3.0m of any adjacent fixed elevation and to within 15mm of proposed grades over any other 3.0 length. Finish grades shall not be uniformly high or low.											
3.1 SURPLUS MATERIAL 1. Remove all excess fill soils and mix stock piles and dispose of all waste materials, trash and debris from the site. 2. Clean up any soil or dirt spilled on any paved surface at the end of each working day. 3. Upon completion of the structural soil mixture installation. Leave area broom-clean. Avoid washing the area until all of the paving has been completed.											
3.2 PREPARATION OF EXISTING GRADE 1. Excavate sub grade to establish tree pit / trench as indicated on contract drawings. Place the structural soil under the paving adjacent to the planting pits, NOT in the planting pits themselves. 2. Areas designated as structural soil tree pits for street tree planting shall be prepared to ninety-five percent (95%) Modified Proctor Density and shall be free of stones, debris, root branches, toxic materials, building materials and other deleterious materials to the approval of the civil engineer.											
3.3 SUB DRAINS 1. Install to requirements of Master Municipal Specifications. Refer to Section 02666, Waterworks, Section 02721, Storm Sewers, and Section 02725, Manholes and Catch Basins 1.1 Install prior to installation of the structural soil mixture 1.2 Co-ordinate all contract drainage work with other drainage on-site 1.3 Confirm location of storm sewer connections with civil engineer.											
3.4 IRRIGATION 1. Install to requirements of Section 02810, Irrigation System. Refer also to Irrigation Drawings 1.1 Install irrigation main lines in co-ordination with installation of the structural soil. Confirm timing at start-up meeting. 1.2 Co-ordinate all contract irrigation work with other civil engineering and drainage on-site 1.3 Confirm location of irrigation connections with civil engineer.											
3.5 MIXING STRUCTURAL SOIL MATERIAL 1. Ensure consistent even distribution of all components by thorough mixing. The ratio of components will vary and may require adjustment to ensure the soil volume is adequate to fill all voids in the stone. 2. Base Ratio of Materials: - 4 cu metre of aggregate stone section 2.2 - 125 cu metre of Growing Medium section 2.1 - 2 kg Stabilizer section 2.3 x Water as required x The amount of water required will vary according to moisture present in growing medium. 3. Combine the stone, growing medium and Stabilizer product into a thorough, homogeneous mixture. Moisten mixture with fine spray of clean potable water while mixing to activate Stabilizer product.											
3.6 MIXING 1. Do not OVER MIX, OVER HANDLING can result in separation of the growing medium from the stone. Further and final mixing will occur during the placement of the material. 2. All mixing shall be performed on a flat hard, level surface approved by the consultant, using the appropriate soil mixing equipment. 3. Prepare sample Structural Soil Mixes to determine ratio of mix components. Submit sample with test results for approval.											


PART THREE - EXECUTION (cont)	
3.7 PLA 1. Subgrade shall be approved by the Consultant prior to placement of the structural soil mixture. 2. Structural soil shall be moist, but not saturated with water when placed. Placement shall be handled to avoid damage to drainage structures, irrigation equipment, concrete structure or pavement. 3. Place Stone mixture in 300mm lifts through entire area of structural soil mixture. 4. Compact each lift of structural soil material with vibrating drum roller to the satisfaction of the civil engineer. 5. Provide Geotechnical Report to confirm compaction. Test to ensure uniform, acceptable compaction rates have been achieved for each lift and in all areas of structural soil mixture. Refer to Quality Assurance, section 15 6. Provide a uniformly firm and level surface allowing for specified depths of road base and / or growing medium to meet finished design grade. 7. Installation of structural soil in the location of the tree is not recommended. Various techniques such as reinforced wood boxes, steel boxes, large diameter PVC pipe, etc. have been employed to allow for sand to be installed at the tree location with the compacted structural soil surrounding the hole. At the time of tree installation, the sand is removed and growing medium (as per Section 2.1) added to surround the root ball	
3.8 INSTALLATION OF FILTER FABRIC 1. After approval of structural soil mixture compaction, install Filter Fabric. 2. Ensure minimum 60cm overlap of all fabric seams and beyond edge of structural soil.	
3.9 GRANULAR BASE MATERIAL 1. Place minimum 75 mm granular base on top of filter fabric over structural soil layer. 2. Compact granular base to 95% Modified Proctor Density. Compaction must be consistent with other surrounding granular base materials. 3. All areas shall be graded to the contours and elevations indicated on the contract drawings. Ensure positive drainage.	
3.10 PROTECTION 1. Protect existing conditions from damage or staining and make good any damage. 2. All damage will be repaired at the expense of the installation contractor.	
3.11 TREE PLANTING 1. Remove structural soil or other backfill material (sand, see comments in section 3.7.7) from the full dimensions of the tree grate area (12m x 12m x depth of root ball). 2. Re compact all material below root ball to original specified density to prevent settling of the root ball in the hole. 3. Ensure tree is planted in the exact centre of the specified planting station straight and true. 4. Install tree in accordance with BCSLA Landscape Standard. Cut away synthetic root ball twine, cut back improperly sized wire baskets, pull back burlap from around trunk etc. 5. Backfill with Growing Medium as per Section 2.1. Ensure the same growing medium used in the structural soil mix is installed as backfill material. 6. Place 50mm depth composted fir/hem bark mulch over the top of the open tree pit area.	
3.12 TREE GRATES 1. Site Furniture and to contract drawings for tree grates, frames and footings.	
3.13 ACCEPTANCE 1. Consultant shall inspect structural soil "in place" and determine acceptance of material, and finish grading prior to paving. 2. Finish grade shall be to within 15mm of proposed grades within 3.0m of any adjacent fixed elevation and to within 15mm of proposed grades over any other 3.0 length. Finish grades shall not be uniformly high or low.	
3.14 SURPLUS MATERIAL 1. Remove all excess fill soils and mix stock piles and dispose of all waste materials, trash and debris from the site. 2. Clean up any soil or dirt spilled on any paved surface at the end of each working day. 3. Upon completion of the structural soil mixture installation. Leave area broom-clean. Avoid washing the area until all of the paving has been completed.	
3.15 SITE PLAN&CLIENT REQUEST 1. Verify that grades are correct. If discrepancies occur, notify Consultant and do not commence work until directed. 2. Excavate French trench to Master Municipal Specification Section 02223, Trenching, Excavation and Compaction allowing for design depth and width of structural soil mix. 2.1 Refer to contract drawings for areas to be trenched and to details for dimensions 2.2 Compact to 95% Modified Proctor Density. 2.3 Subgrade elevations shall slope parallel to the finished grades and/or toward the subsurface drain lines as indicated on the civil engineering drawings. 4. Do not proceed with the installation of the structural soil material until all walls, curbs, and utility work in the area has been installed. Structural elements or design features that are dependent on the structural soil mixture for support may be postponed until after the installation of the mixture. 5. Re-compact disturbed subgrade to requirements of master municipal specifications and civil engineering drawings.	
3.16 SURFACE DRAINAGE 1. Install to requirements of Master Municipal Specifications. Refer to Section 02666, Waterworks, Section 02721, Storm Sewers, and Section 02725, Manholes and Catch Basins 1.1 Install prior to installation of the structural soil mixture 1.2 Co-ordinate all contract drainage work with other drainage on-site 1.3 Confirm location of storm sewer connections with civil engineer.	
3.17 IRRIGATION 1. Install to requirements of Section 02810, Irrigation System. Refer also to Irrigation Drawings 1.1 Install irrigation main lines in co-ordination with installation of the structural soil. Confirm timing at start-up meeting. 1.2 Co-ordinate all contract irrigation work with other civil engineering and drainage on-site 1.3 Confirm location of irrigation connections with civil engineer.	
3.18 MIXING STRUCTURAL SOIL MATERIAL 1. Ensure consistent even distribution of all components by thorough mixing. The ratio of components will vary and may require adjustment to ensure the soil volume is adequate to fill all voids in the stone. 2. Base Ratio of Materials: - 4 cu metre of aggregate stone section 2.2 - 125 cu metre of Growing Medium section 2.1 - 2 kg Stabilizer section 2.3 x Water as required x The amount of water required will vary according to moisture present in growing medium. 3. Combine the stone, growing medium and Stabilizer product into a thorough, homogeneous mixture. Moisten mixture with fine spray of clean potable water while mixing to activate Stabilizer product.	
3.19 MIXING 1. Do not OVER MIX, OVER HANDLING can result in separation of the growing medium from the stone. Further and final mixing will occur during the placement of the material. 2. All mixing shall be performed on a flat hard, level surface approved by the consultant, using the appropriate soil mixing equipment. 3. Prepare sample Structural Soil Mixes to determine ratio of mix components. Submit sample with test results for approval.	
3.20 COORDINATION 1. Coordinate all work with other contractors and civil engineering to ensure smooth and timely completion of the project.	
3.21 SUBMISSION 1. Submit all required documentation and samples to the Consultant for review and approval.	
3.22 APPROVAL 1. Upon receipt of all required documentation and samples, the Consultant shall issue a formal written approval.	
3.23 RECORDS 1. Maintain all records and documentation required by the Consultant and other relevant authorities.	
3.24 PAYMENT 1. Payment will be made in accordance with the terms and conditions of the contract.	
3.25 WARRANTY 1. Provide a written warranty for the structural soil mixture installed.	
3.26 INSPECTION 1. Provide access to the site for inspection by the Consultant and other relevant authorities.	
3.27 COMPLAINTS 1. Provide a written response to any complaints received.	
3	



APLIN MARTIN

ENGINEERING ARCHITECTURE PLANNING SURVEYING

Aplin & Martin Consultants Ltd.
#1818 – 1177 West Hastings Street, Vancouver, B.C. V6E 2K3
Tel: (604) 678-9434, Fax: (604) 597-9061, Email: general@aplinmartin.com



SITE LOCATION PLAN

SCALE 1:2000

DRAWING INDEX

- 18-010-01 COVER SHEET
- 18-010-02 KEY PLAN & GENERAL NOTES
- 18-010-03 SERVICING & GRADING PLAN
- 18-010-04 TRUCK TURNING PLAN

CLIENT:

DISTRICT GROUP

SUITE 200 - 8809 HEATHER STREET, VANCOUVER, BC V6P 3T1
PH. 604-322-5762

NOT FOR CONSTRUCTION


PROJECT:

PARKWAY - MIXED-USE DEVELOPMENT

1050 PANDORA AVENUE & 1518 COOK STREET, VICTORIA, BC

MUNICIPAL PROJECT No. XXX

APLIN & MARTIN PROJECT No. 18-010



NOT FOR CONSTRUCTION

NOTICE TO CONTRACTOR

IT IS THE RESPONSIBILITY OF THE CONTRACTOR'S SURVEYOR TO VERIFY THAT ALL
LEGAL SURVEY DIMENSIONS SHOWN ON THE ENGINEERS DRAWINGS AGREE WITH THOSE
ON THE REGISTERED LEGAL SURVEY PLAN. SHOULD THERE BE ANY DISCREPANCIES,
THEN IMMEDIATELY NOTIFY THE ENGINEER OF RECORD

LEGAL DESCRIPTION: SITE PLAN OF AMENDED LOT 14 (DD 106561 I), LOTS 15 & 16, LOT 2, PLAN VIP75915 OF SUBURBAN LOT 15					
B.M. MONUMENT NO. 16-64A LOCATED AT COOK STREET & PANDORA AVENUE			ELEVATION: 27.355m		
REV. NO.	DESCRIPTION	DR	CH	DATE	APP
03	DEVELOPMENT PERMIT COMMENTS ADDRESSED	CL	SL	11/09/19	SL
04	ISSUED FOR 60% BP SUBMISSION	VG	SL	15/10/19	SL
05	ISSUED FOR 90% BP SUBMISSION	VG	SL	06/11/19	SL
06	ISSUED FOR 100% BP SUBMISSION	VG	SL	25/11/19	SL
07	TREE REMOVED ON COOK STREET	CL	SL	20/03/20	SL






APLIN MARTIN
ENGINEERING ARCHITECTURE PLANNING SURVEYING

Aplin & Martin Consultants Ltd.
#1818 – 1177 West Hastings Street, Vancouver, B.C. V6E 2K3
Tel: (604) 678-9434, Fax: (604) 597-9061, Email: general@aplinmartin.com

CLIENT:

DISTRICT GROUP

PROJECT: PARKWAY - MIXED USE DEVELOPMENT




SERVICING & GRADING PLAN


JECT NO.	SCALE : HORZ. 1: 250 VERT. N/A
WING NO.	A & M DRAWING 18-010 - 03

SIGN: VG CHECK: SL
DRAWN: VG/CL APPR: SL
A & M FILE:


18-010	
DRAWING DATE:	
FEBRUARY 2019	
SHEET NO.	REV.
03 OF 04	07



TURN ROUTE 1 – DIRECT ENTRY



MSU
meters
Width : 2.60
Track : 2.60
Lock to Lock Time : 6.0
Steering Angle : 40.2



TURN ROUTE 1 – BACK-IN ENTRY

NOT FOR CONSTRUCTION

NOTICE TO CONTRACTOR

IT IS THE RESPONSIBILITY OF THE CONTRACTOR'S SURVEYOR TO VERIFY THAT ALL LEGAL SURVEY DIMENSIONS SHOWN ON THE ENGINEERS DRAWINGS AGREE WITH THOSE ON THE REGISTERED LEGAL SURVEY PLAN. SHOULD THERE BE ANY DISCREPANCIES, THEN IMMEDIATELY NOTIFY THE ENGINEER OF RECORD.

LEGAL DESCRIPTION: SITE PLAN OF AMENDED LOT 14 (DD 106561 1), LOTS 15 & 16, LOT 2, PLAN VIP75915 OF SUBURBAN LOT 15									
B.M. MONUMENT NO. 16-64A LOCATED AT COOK STREET & PANDORA AVENUE					ELEVATION: 27.355m				
REV. NO. DESCRIPTION DR CH DATE APP									
03	DEVELOPMENT PERMIT COMMENTS ADDRESSED	CL	SL	11/09/19	SL				
04	ISSUED FOR 60% BP SUBMISSION	VG	SL	15/10/19	SL				
05	ISSUED FOR 90% BP SUBMISSION	VG	SL	06/11/19	SL				
06	ISSUED FOR 100% BP SUBMISSION	VG	SL	25/11/19	SL				
07	TREE REMOVED ON COOK STREET	CL	SL	20/03/20	SL				



Amlin & Martin Consultants Ltd.
#1818 - 1177 West Hastings Street, Vancouver, B.C. V6E 2K3
Tel: (604) 678-9434, Fax: (604) 597-9061, Email: general@aplinmartin.com

CLIENT: DISTRICT GROUP SUITE 200 - 8809 HEATHER STREET, VANCOUVER, BC V6P 3T1 PH. 604-322-5762	PROJECT: PARKWAY - MIXED USE DEVELOPMENT 1050 PANDORA AVENUE & 1518 COOK STREET, VICTORIA BC	STAMP: PROFESSIONAL ENGINEER S.A. LEWIS #23811 2020-03-20	TITLE: TRUCK TURNING PLAN	DESIGN: VG CHECK: SL DRAWN: VG/CL APPR: SL A & M FILE: 18-010
REV. NO. DESCRIPTION DR CH DATE APP	PROJECT NO. *	SCALE : HORIZ. 1:250 VERT. N/A	DRAWING NO. *	A & M DRAWING NO. 18-010-04 SHEET NO. 04 OF 04 REV. 07

0 2 1:250 12m